

BS-0981



Features



- 19" 1U Fanless Rack mount PC
- Intel[®] Celeron N3350 SoC
- 2 x LAN, 6 x USB, 4 x COM, 1 x VGA, 1 x DP
- Supports 1 x 2.5" HDD, 1 x full-sized mSATA

Specifications

System		System Front View & Rear View	1
CPU Support	Intel [®] Celeron N3350: 6w, 2C, 2.4GHz		
Memory Support	1 x SO-DIMM DDR3L, supporting 1600/1866MHz (up to 8G)		
API/SW/FW	Watchdog / HW monitor / fTPM		
Storage Support	1 x 2.5" SATAIII HDD or SSD	Front View	
Power Input	DC 12V only		
Power Adapter	60W adapter w/ lockable 3 pin terminal block (optional)	Power Button USB	3 Po
Operating System	Windows 10 64bit		
Expansion Slots	1 x full-sized mSATA slot (with SATA and USB signal)	- 0 • 8 • • •	
	1 x full-sized mPCIe slot (with PCIe and USB signal)	-	•
System Weight	Approx. 1.5 kg		
Dimensions	480 x 45 x 250 mm (W x H x D)		

Rear	View
(Cai	VICVV



USB Ports

Kold ·

I/O Ports (Front side) USB 2 x USB 2.0 LED 1 x HDD LED Power On/Off 1 x power button

I/O Ports (Rear side)

12V DC In Display 1 x VGA 1 x DP LAN 2 x GIGA LAN Audio 1 x Line Out USB 4 x USB 3.0 Serial Ports COM 1: RS232 COM 2: RS232/422/485 selectable und		
1 x DP LAN 2 x GIGA LAN Audio 1 x Line Out USB 4 x USB 3.0 Serial Ports COM 1: RS232 COM 2: RS232/422/485 selectable und	Power Input	3 pin DC In terminal block (lockable), supportin 12V DC In
Audio 1 x Line Out USB 4 x USB 3.0 Serial Ports COM 1: RS232 COM 2: RS232/422/485 selectable und	Display	
USB 4 x USB 3.0 Serial Ports COM 1: RS232 COM 2: RS232/422/485 selectable und	LAN	2 x GIGA LAN
Serial Ports COM 1: RS232 COM 2: RS232/422/485 selectable und	Audio	1 x Line Out
COM 2: RS232/422/485 selectable und	USB	4 x USB 3.0
	Serial Ports	COM 1: RS232 COM 2: RS232/422/485 selectable under BIOS COM 3: RS232 w/ RI/5V/12V selectable by jum COM 4: RS232 w/ RI/5V/12V selectable by jum

Environment

Operating Temp.	0°C~40°C (32°F~104°F)
(Ambient with airflow)	
Storage Temp.	-40°C~85°C (-40°F~185°F)
Humidity	20%~90%

Applications

Automation
• Retail
• Transportation
• Information

* All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information. For detail mechanics drawing, please contact our sales.

No. 24, Lane 365, Yang Kuang Street, Nei Hu District Taipei 114, Taiwan TEL: +886-2-8751-1111

950 Fee Ana St, Suite B Placentia, CA 92870 TEL: +1-714- 996-7200

OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013 TEL: +81-3-5753-8411

Weststrasse 20a, 40721 Hilden Düsseldorf, Germany TEL: +49 (0) 2103-41898-0

PROX SYSTEMS Spain S.L. C/Albasanz 14 Bis 2ºD, 28037 Madrid, Spain TEL: (+34) 917648559