


Packing Checklist

If you discover any item below are damaged or lost, please contact your vendor immediately.

\square	MH-0616 Handy Tablet	x1
\square	This Quick Reference Guide	x1
\square	AC Power Adaptor	x1
	Hand Strap (optional)	x1

Reliability and Environment				
ESD	Contact +/-8kV & Air +/- 15kV			
EMI	Class B			
IP Rating	IP65 per IEC 60529			
Drop Test	1.2m per MIL-STD-810H			
Tumble Test	1000 tumbles, 0.5m per IEC 60068-2-32			
Shock / Vibration	Per MIL-STD-810H			
Operating Temp.	-10°C~50°C (Discharging) & 0°C~40°C (Charging)			
Storage Temp.	-20°C~60°C			
Humidity	10%~90% non-condensing			
Certificate	CE, FCC, BSMI, PSE, Battery with			
	UN 38.3 & IEC 62133			

	MH-0616			
	MH-0010			
Specifi	cations			
CPU Type	Qualcomm [®] S660 Octa-Cores 2.2GHz			
Operating System	Android 10			
Memory + Storage	4+ 64GB eMCP			
Audio	1 x 0.8W Speaker & 2 x Digital Mic			
Sensor	G-Sensor, Ambient Light Sensor			
LED Indicators	1 x tri-color LED (Green/ Yellow/ Red) for Power/ Battery status indication			
Buttons	1 x Power button, 1 x Function key, 2 x Scan buttons, 1 x Volume+, 1 x Volume-			
Battery	1S1P 3.85V/ 4380mAh/ 16.8Wh, Removable Battery, up to 10 hours operating (per JEITA test v2.0)			
AC Adapter	Quick Charge™ 3.0 30W for tablet & Charging Stand			
USB Cable	1 x USB Type-C cable for Charging with AC Adapter & Data Transmission			
Dimensions (W x H x D)	89 x 168 x (18.6-19.6) mm (Tablet only)			
Weight	330 g (Tablet only)			
Display Specifications				
Size	6"			
Resolution	720 x 1280 pixels (High Definition)			
Brightness	500 nits for Sunlight readable (Backligt Lifetime: 30,000 hours)			
Touch	P-CAP Multi-Touch with Anti-Fingerprint & Corning Gorilla Glass (Support Finger/ Stylus/ Glove/ Raindrop)			
Viewing Angle	80 / 80 / 80 / 80			
Bonding Technology	LCD Optical Clear Adhesive direct bonding with Touch			



USB	1 x USB 3.0 Type-C for Charging with Quick Charge [™] 3.0 & Data Transmission,				
	1 x USB 2.0 with 5-pin internal connector for Expansion Device with customized				
	back cover (such as 3-in-1 Card Reader)				
MicroSD Slot	1 x internal slot for MicroSD up to 128GB				
Nano-SIM Slot	1 x internal slot for 4G LTE				
Pogo Pin	4 x Pin (for Cradle Charger)				
Communications					
WLAN and Bluetooth	Wi-Fi 802.11 a/b/g/n/ac (WiFi 5) / Bluetooth 5.0				
GNSS	GPS, GLONASS (optional)				
WWAN	4G LTE for North America/ Europe/ Taiwan/ Japan (Optional)				
Optional Peripherals & Accessories					
1D/2D Barcode	Honeywell N6703				
Camera	13MP Rear Camera with Auto-Focus, Flashlight				
3D Camera	Embedded Time of Flight (ToF) Sensor for dimension measurement				
RFID	Support ISO14443A/ MifaireS50(R/W)/ ISO14443B Des Fires(Read UID Only)				
	ISO15693 I-Code SLI (R/W)/ ISO18092 SONY Felica/ Mifare Classic1K/ 4K type1)/				
	Mifare Ultralight (Type 2) & Mifare DesFire EV1/EV2/EV3 (Type4)				
Charging Stand	For tablet & Battery charging				
Protective Case	Support 1.8m Drop test				
Hand Strap	Attach to tablet handle Easily detachable w/clips underneath Snaps securely in place				
Stylus	Capacitive Stylus				
TP Protector	9H glass Touch Panel Protector				

I/O Ports

Bottom View



USB Type-C

Prevent battery overdischarge

- (1) The "Shipping Mode" for each tablet installed with battery has been activated prior to the shipment out of the factory, and the tablets can be stored for about 6 months under normal conditions. If the customers need to store the purchased tables (with battery) for more than 6 months, please connect the Cradle to each tablet and make sure the battery has been charged to 60% before the tablets can be put into storage. (It takes about 2.5 hours to charge a tablet to 60%.)
- (2) If the battery unit needs to be stored in the warehouse for more than 6 months, please make sure you use the battery charger to recharge the battery to 60% for every 6 months.



We recommend to contact your qualified technician if you meet any issues. Please recycle your device and battery in accordance with local regulations.